
4" CVS Safety Gauge

Safety Gauge Design:

This gauge is designed with many safety features to minimize personnel injury, property damage and more importantly, gauge failures. Our manufacturing specifications require that our gauge must have the following capabilities.

1. 130% full scale pressure without loss of accuracy.
2. 300% full scale pressure without rupture of the bourdon tube.
3. Conform to accuracy specifications BSS 1780.

Glycerine or Silicone filled Gauges:

Glycerine and silicone are viscous in nature and will act as a dampening agent, and provide excellent lubrication minimizing wear on internal components. Corrosive and dirty atmospheres are virtually eliminated by having the internal components immersed in fluid. When compared to a dry gauge a liquid filled gauge will last approximately 10 times longer in any given application.

Size:

4" (100mm)

Ranges (All ranges not stocked)

Vacuum / Compound
Pressure from 15 psi to 30,000 psi
100 kPa to 200,000 kPa

Operating Temp.

-40° C to 95° C
-40° F to 200° F)

Special Features:

All Stainless steel construction (316 S ST)
304 Stainless steel bayonet ring
Window-Laminated safety glass
Pulsation Dampener Plate
Adjustable Pointer
Blowout Protection
Sealed Case
316 Stainless steel Movement

Dial: White aluminum with black/red lettering



Material: 316 stainless steel

All our gauges in excess of 1000 psi or 7000 kPa have a spiral bourdon tube.

Mounting Configuration: Bottom Mount (BM)

Window Gasket: Neoprene or Viton

Order Options: (Min. order may apply)

Custom Dial layout

Silicone and Fluorolube fill

316 SS Threaded Restrictor

Additional pressure scales available

-kPa, Bar, Kg/cm² and dual scales

Drag Pointer


We warrant our pressure gauges to be free of defects in materials and workmanship. Replacement of any defective gauge will be made at no cost to the purchaser.

We will repair any of our gauges that have malfunctioned. These units will receive cleaning, four point calibration, testing, and thorough inspection before leaving CVS Controls Ltd.

For applications where temperatures are below -40° C to 95° C (-40° F to 200° F). Please consult with a CVS sales representative.

Warning: Glycerine filled gauges should **NOT** be used in chlorine service.

4" CVS Safety Gauge Dimensional Data



MODEL	WEIGHT	KEY	A	B	C	D	E	F
233.54 4"	1.10 lbs. +0.66 lbs. if filled	mm	100	87	49.5	8	100	15.5
		in	4	3.43	1.95	0.31	3.94	0.61