



Head Office
1107 8A Street
Nisku, Alberta
T9E 7R3
Ph: 780.437.3055

Calgary Office
3516 114 Avenue SE
Calgary, Alberta
T2Z 3V6
Ph: 403.250.1416
Fax: 403.291.9487

CVS V308 Isolation Valve 2 Inch Class 2500

The CVS Series V308 Isolation Valve is a quarter turn fully open or fully closed valve suitable for use to stop the flow of gas, liquid, slurry or powder.

Typically operated in the fully open or fully closed positions to protect in an emergency, or provide shutoff protection for safe maintenance



Features:

CRN OC17433.2

Compliant with ASME B16.34 and NACE MRO175

Inspected and tested to API 598


End to End connections comply to manufacturing standards

Threaded Ends - ASME B1.20 NPT

Flanged Ends – ASME B16.5

-50°F to 250°F (-46°C to 121°C)

CVS 2 Inch 2500 V308 Isolation Valve – Assembly Dimensions



| Item | Description | Material | Item | Description | Material |
|------|---------------|-----------------------|------|-----------------|------------------|
| 1 | Cap 1 | A350 LF2 Class 1 | 10 | Lockhole Flange | WCB |
| 2 | Seat | PEEK | 11 | Body | A350 LF2 Class 1 |
| 3 | Ball | 316 SST Chrome Coated | 12 | O-Ring | Viton GLT |
| 4 | Thrust Washer | Delrin | 13 | Washer | RTFE |
| 5 | Packing | RTFE (15% GFT) | 14 | Handle | WCB |
| 6 | Gland | 316 SST | 15 | Screw | 410 HT |
| 7 | Bevel Washer | 304 SST | 16 | Plug | A105 |
| 8 | Nut | A2-70/CS+Zn | 17 | Cap 2 | A350 LF2 Class 1 |
| 9 | Stem | 17-4ph | 18 | O-Ring | Viton GLT |